

TABLAS Y CURVAS

APEC CP15 (RG-38) Super Cañon 1 1/2 Pulg. FNPT círculo parcial y completo 25° (22-35 mts radio) (incluye boquillas 5,12,14,16,18)

No de fábrica CP15

NOTA:

Registro iia 12570

MAIN NOZZLE Ø(mm)	SPREADER NOZZLE Ø(mm)	PRESSURE Kg.	CASTING RADIUS	DISCHARGE	
				m ³ /h	LPM
12	5	2.0	22	8.6	143
		3.0	24	10.5	175
		4.0	26	12.1	202
		5.0	29	13.6	227
14	5	2.0	23	11.2	187
		3.0	25	13.9	232
		4.0	28	15.8	263
		5.0	30	17.7	295
16	5	2.0	24	14.2	237
		3.0	26	17.4	290
		4.0	29	20.1	335
		5.0	32	22.5	375
18	5	3.0	27	21.6	360
		4.0	30	24.9	415
		5.0	33	27.8	463
		6.0	35	30.5	508

Mar de las Antillas #209, Col. Central, Monterrey, NL 64190 México

Tel. (8) 370-0801 (8) 115-2361 (8) 115-2369 Fax (8) 373 4336 E-mail iia@deriego.com

iia

www.deriego.com