

TABLAS Y CURVAS

APEC Super Cañon 2 Pulg. FNPT circulo parcial y completo 25° (20-43 mts radio) (incluye boquillas 8,12,14,16,18,20)

No de fábrica CP20

NOTA:

Registro iia 12572

MAIN NOZZLE Ø(mm)	SPREADER NOZZLE Ø(mm)	PRESSURE Kg.	CASTING RADIUS	DISCHARGE	
				m ³ /h	LPM
12	8	1.5	20	9.5	159
		2.0	23	11.0	184
		3.0	27	13.4	224
		4.0	30	15.5	259
14	8	2.0	25	13.8	230
		3.0	29	16.8	280
		4.0	32	19.5	325
		5.0	34	21.8	364
16	8	2.0	27	16.9	282
		3.0	31	20.6	344
		4.0	34	23.9	399
		5.0	37	26.7	446
18	8	2.0	28	20.6	343
		3.0	33	26.0	434
		4.0	36	30.3	506
		5.0	40	33.6	561
20	8	2.0	29	24.6	411
		3.0	34	31.2	520
		4.0	38	36.3	606
		5.0	43	39.4	657

Mar de las Antillas #209, Col. Central, Monterrey, NL 64190 México

Tel. (8) 370-0801 (8) 115-2361 (8) 115-2369 Fax (8) 373 4336 E-mail iia@deriego.com



www.deriego.com