

SPRAYS -RES/COM SPECIFICATION

iStop™ 63XR RETROFIT KITS

63XR-02

2½" (6,3 cm)
Retrofit iStop™ Kit

63XR-04

4" (10,2 cm)
Retrofit iStop™ Kit

63XR-06

6" (15,2 cm)
Retrofit iStop™ Kit

63XR-12

12" (30,5 cm)
Retrofit iStop™ Kit

Accessories

6318

Piston Extension

6319

Anti-drain valve (ADV)

6390RWC

Identifies reclaimed water site

6300

Shrub Adapter

7300

Adjustable Bubbler

8819

Brass automatic drain valve

63XR




6390RWC



7300



6319



6318



6300



8819



ACCESSORY FEATURES

iStop™ 63XR RETROFIT KIT

- Shuts off if the nozzle is removed
- Shuts off if the riser is broken at any point above the top level of the cap
- Retrofit any existing 6300 sprayhead with new iStop™

6318 (Not Shown)

- Adds 6" (15, 24 cm) to any series pop-up
- Perfect for landscape areas that need extra clearance
- It threads directly onto the top of the piston and accepts all Signature® spray nozzles

6319

- Anti-drain valve (ADV) helps eliminate low head drainage and puddling. Holds back up to 10 ft (3 m) difference in elevation.

6300

- Adapt from ½" (12,7mm) NPT to a standard female thread spray nozzle

7300

- Provides an umbrella pattern that can be adjusted with a stainless steel set screw
- Bubbler installs on standard ½" (12,7 mm) riser and has a maximum flow of 4.9 gpm (7,6 l/min) at 18" (45 cm) radius

8819

- Prevents underground line breakage due to freezing
- Solid brass body
- Automatically opens when line pressure drops below three psi
- ½" male threads
- 5 year warranty on materials and workmanship

Pressure	Radius ¹		Discharge ¹	Model	Pressure		Radius ¹		Discharge ¹
	PSI	FT			GPM	BAR	kPa	m	
20	0.8	2.9	7300 FULL (360°)		1.4	138	0.2	11.0	0.66
30	0.9	3.5			2.1	207	0.3	13.2	0.79
40	1.1	4.1			2.8	276	0.3	15.5	0.93
50	1.2	4.5			3.5	345	0.4	17.0	1.02
60	1.2	4.9			4.2	414	0.4	18.5	1.11

¹ Radius and flow can be reduced with adjustment screw.

SIGNATURE CONTROL SYSTEMS, INC.

WORLD HEADQUARTERS

18 Goodyear • Suite 110
Irvine • California • 92618
Tel: 949.580.3640
Fax: 949.580.3645

MANUFACTURING FACILITY

8800 N. Allen Rd.,
Peoria • Illinois • 61615
Tel: 949.580.3640
Fax: 949.580.3645

EUROPE & MIDDLE EAST

5 rue de la Vallée Yart
78640 Saint Germain de la Grange
France
Tel: +33.13.489.9056
Fax: +33.13.489.6025

REGIONAL OFFICES

ASIA
NanXian Plaza • MinZhi Street • Shenzhen,
Guangdong Province • 518131
Tel: (86) 136.00419465 • Fax: (86) 755.83275012

SOUTH AMERICA
Av Paseo Los Bravos 6000 • Lo Barnechea
Santiago • Chile
Tel/Fax: +56 229.556220

MEXICO, CENTRAL AMERICA
Ribera Escondida 118 • Riberas Del Campestre
38080 Celaya • Gto. • Mexico
Tel/Fax: +52 (461) 614.2322

AFRICA
P.O. Box 1260 • Strubensvalley 1735
Roodepoort • South Africa
Office & Mobile: +27 82 553 9093 • Fax: 086 670 6318

USA Toll Free: 866.4SIGNATURE

www.SignatureControlSystems.com