

6095 LOW ANGLE

13° trajectory (optional for 6000 series only)

(Part Numbers - 6095)

Nozzle color



Pressure	Max Radius	Min Radius	Discharge	Precipitation Rate ¹		Nozzle Number	Pressure		Max Radius	Min Radius	Discharge	Precipitation Rate ¹		
				PSI	FT		FT	GPM				IN/HR■	IN/HR▲	BAR
20	26	20	0.9	0.26	0.32	4	1.4	138	7.9	5.9	3.4	0.20	6.5	8.1
35	33	25	1.3	0.23	0.29		2.5	242	10.1	7.5	4.9	0.30	5.8	7.3
50	34	26	1.5	0.25	0.31		3.5	345	10.4	7.8	5.7	0.34	6.3	7.9
20	26	20	1.1	0.31	0.39	5	1.4	138	7.9	5.9	4.2	0.25	8.0	9.9
35	33	25	1.4	0.25	0.31		2.5	242	10.1	7.5	5.3	0.32	6.3	7.8
50	35	26	1.7	0.27	0.33		3.5	345	10.7	8.0	6.4	0.39	6.8	8.5
20	26	20	1.4	0.40	0.50	6	1.4	138	7.9	5.9	5.3	0.32	10.1	12.6
35	33	25	1.9	0.34	0.42		2.5	242	10.1	7.5	7.2	0.43	8.5	10.6
50	36	27	2.3	0.34	0.43		3.5	345	11.0	8.2	8.7	0.52	8.7	10.8
20	31	23	2.5	0.50	0.62	7	1.4	138	9.5	7.1	9.5	0.57	12.7	15.9
35	35	26	3.1	0.49	0.61		2.5	242	10.7	8.0	11.7	0.70	12.4	15.4
50	37	28	3.5	0.49	0.61		3.5	345	11.3	8.5	13.2	0.79	12.5	15.6
35	32	24	3.2	0.60	0.75	8	2.5	242	9.8	7.3	12.1	0.73	15.3	19.1
50	38	29	4.0	0.53	0.67		3.5	345	11.6	8.7	15.1	0.91	13.6	16.9
65	39	29	4.7	0.60	0.74		4.6	449	11.9	8.9	17.8	1.07	15.1	18.9
35	34	26	3.9	0.65	0.81	9	2.5	242	10.4	7.8	14.8	0.89	16.5	20.6
50	37	28	4.9	0.69	0.86		3.5	345	11.3	8.5	18.5	1.11	17.5	21.8
65	40	30	5.7	0.69	0.86		4.6	449	12.2	9.2	21.6	1.29	17.4	21.7
35	33	25	5.1	0.90	1.12	10	2.5	242	10.1	7.5	19.3	1.16	22.9	28.6
50	39	29	6.4	0.81	1.01		3.5	345	11.9	8.9	24.2	1.45	20.6	25.7
65	42	32	7.5	0.82	1.02		4.6	449	12.8	9.6	28.4	1.70	20.8	25.9